

Bakery Line Single

Compressor cooling



Product description

Bakery Line Single is manufactured for the distribution of cold bakery products. The box is made according to the standard dimensions of bakery trays. The box is designed with ScanBox ExP construction that combines optimized insulation performance with high operational reliability and environmentally conscious choices.

The box is equipped with compressor cooling that provides effective cooling down to 3°C in 30 minutes. Digitally adjustable temperatures ensure excellent

food quality control. ScanBox Bakery Line Single has capacity for 12 baking trays according to the standard dimensions of 400x600 or 450x600.

Equipped with ScanBox Digital Control, excenter lock, solid door, 160 mm lockable wheels, removable 'L' shaped runners with 100 mm spacing, black RAL 9005, 220-230V single phase with Type F electrical plug. The equipment can be easily adapted as required through available extra options.

Do you want to know more?

Contact us at info@scanbox.se
or +46 (0)454-30 83 00

ScanBox
Bringing your food with care

Technical specification

MODEL SERIE: Bakery Line Single - Compressor cooling



Product models	BBSCC40	BBSCC45
Properties		
Regulator	Digital	Digital
Cooling system	Compressor	Compressor
Capacity		
Tray system		
Distance between racks (mm)	100	100
Number of 65mm trays	12	12
Maximum load weight per rack (kg)	9	9
Distance to the first rack (mm)	20	20
Physical Attributes		
Inside depth (mm)	681 mm	681 mm
Inside width (mm)	487 mm	487 mm
Inside height (mm)	1287 mm	1287 mm
Outside depth (mm)	950 mm	950 mm
Outside width (mm)	675 mm	675 mm
Outside height (mm)	1677 mm	1677 mm
Volume (l)	427 l	427 l
Net weight (kg)	94 kg	94 kg
Spiral Cord	4.5 m	4.5 m
Electrical Attributes		
Rated voltage (V)	220-240V / 1 phase	220-240V / 1 phase
Rated frequency (Hz)	50-60 Hz	50-60 Hz
Power Rating (A)	1.55 kW	kW
Power (W)	180 W	180 W
IP code	22	22

Equipment & Accessories

MODEL SERIE: Bakery Line Single - Compressor cooling



Castors & Brakes

Default	Castors 160 mm swiveling with brake
1000007	Castors 160 mm, stainless steel, swiveling with brake
1000009	Castors 160 mm, all swiveling w. brakes
1000010	Castors 160 mm, stainless steel, all swiveling w. brakes
1000016	Castors 200 mm w. central brake
1000008	Castors 160 mm, dish washable w. brake
1000004	Castors 200 mm swiveling with brake
1000005	Castors 160 mm reinforced, swiveling with brake
1000015	Castors 160 mm w. central brake
1000006	Castors 200 mm reinforced, swiveling with brake
1000017	Castors 160 mm stainless steel w. central brake

Exterior

Default	Black (RAL 9005)
303010-2	Signature Logo
302030-1	Grey (RAL 7042)
950001	Signature Cover
302020-1	Red (RAL 3003)

Electric System

Default	220-240V - Type CEE 7/7
898294-1	220-240V - Type K
905390	220-240V - Type H
4000556	220-240V - Type L
898208-1	220-240V - Type J
90001	220-240V - Type C
898205-1	220-240V - Type G
905817	220-240V - Type I
898202-1	220-240V - Type G 1,5mm ²
90004	220-240V - Type O
898203-1	220-240V - Type I
90002	220-240V - Type D
4000241	220-240V - Type M

Door

Default	Solid
93002	Glass window

Door Handle

Default	Excenter Lock
---------	---------------

Logistic System

361020	Central Brake
302002-2	Tow Bar Stainless Steel
302001-3	Tow Bar VE

Accessories

400010-1	Card Holder
----------	-------------

www.scanbox.se

Visiting adress ScanBox AB, Ekångsvägen 1. SE-293 40 Olofström, Sweden
Post adress ScanBox AB, P.O. Box 13. SE-293 21 Olofström, Sweden
Telephone +46 (0) 454 30 83 00 | Fax +46 (0) 454 30 83 30
Email info@scanbox.se | VAT SE556446828701

ScanBox
Bringing your food with care