Bakery Line Single

Fan heating





Product description

Bakery Line Single is manufactured for the distribution of hot bakery products. The box is made according to the standard dimensions of bakery trays. The box is designed with ScanBox ExP construction that combines optimized insulation performance with high operational reliability and environmentally conscious choices.

The box is equipped with fan heating that provides fast and uniform heat distribution and can reach operating temperatures of up to 90°C in 30 minutes. Adjustable temperature and ventilation ensure

excellent food quality control. ScanBox Bakery Line Single has capacity for 12 baking trays according to the standard dimensions of 400x600 or 450x600.

Equipped with ScanBox Digital Control, excenter lock, solid door, 160 mm lockable wheels, removable 'L' shaped runners with 100 mm spacing, black RAL 9005, 220-230V single phase with Type F electrical plug. The equipment can be easily adapted as required through available extra options.



Technical specification

MODEL SERIE: Bakery Line Single - Fan heating



Product models	BBSHF40	BBSHF45		
Properties				
Regulator	Digital	Digital		
Heating system	Element with fan & ventilation (std)	Element with fan & ventilation (std)		
Capacity				
Tray system				
Distance between racks (mm)	100	100		
Number of 65mm trays	12	12		
Maximum load weight per rack (kg)	9	9		
Distance to the first rack (mm)	20	20		
Physical Attributes				
Inside depth (mm)	681 mm	681 mm		
Inside width (mm)	487 mm	487 mm		
Inside height (mm)	1287 mm	1287 mm		
Outside depth (mm)	880 mm	880 mm		
Outside width (mm)	675 mm	675 mm		
Outside height (mm)	1677 mm	1677 mm		
Volume (I)	427	427		
Net weight (kg)	80 kg	80 kg		
Spiral Cord	4.5 m	4.5 m		
Electrical Attributes				
Rated voltage (V)	220-240V / 1 phase	220-240V / 1 phase		
Rated frequency (Hz)	50-60 Hz	50-60 Hz		
Power Rating (A)	7.98 kW	7.98 kW		
Power (W)	1800 W	1800 W		
IP code	44	44		



Equipment & Accessories MODEL SERIE: Bakery Line Single - Fan heating



302030-1

302020-1

950001

Castors & Brakes		
	Default	Castors 160 mm swiveling with brake
	1000007	Castors 160 mm, stainless steel, swiveling with brake
	1000009	Castors 160 mm, all swiveling w. brakes
	1000010	Castors 160 mm, stainless steel, all swiveling w. brakes
	1000016	Castors 200 mm w. central brake
	1000008	Castors 160 mm, dish washable w. brake
	1000004	Castors 200 mm swiveling with brake
	1000005	Castors 160 mm reinforced, swiveling with brake
	1000015	Castors 160 mm w. central brake
	1000006	Castors 200 mm reinforced, swiveling with brake
	1000017	Castors 160 mm stainless steel w. central brake
	Exterior	
	Default	Black (RAL 9005)
	303010-2	Signature Logo

Grey (RAL 7042)

Signature Cover

Red (RAL 3003)

Electric System	
Default	220-240V - Type CEE 7/7
898294-1	220-240V - Type K
905390	220-240V - Type H
4000556	220-240V - Type L
898208-1	220-240V - Type J
90001	220-240V - Type C
898205-1	220-240V - Type G
905817	220-240V - Type I
898202-1	220-240V - Type G 1,5mm²
90004	220-240V - Type O
898203-1	220-240V - Type I
90002	220-240V - Type D
4000241	220-240V - Type M
Door	
Default	Solid
93002	Glass window
Door Handle	
Default	Excenter Lock
Logistic System	
361020	Central Brake
302002-2	Tow Bar Stainless Steel
302001-3	Tow Bar VE

361020	Central Brake
302002-2	Tow Bar Stainless Steel
302001-3	Tow Bar VE
Accessories	
400010-1	Card Holder

www.scanbox.se

