

Banquet Line Combo

Fan heating



Product description

The Banquet Line Combo is manufactured to hold and transport hot food in two separate compartments with GN 2/1 capacity. The box is designed with ScanBox ExP construction that combines optimized insulation performance with high operational reliability and environmentally conscious choices.

The lower and upper compartments of the box form individual temperature zones with fan heating that provides fast and uniform heat distribution and can reach operating temperatures of up to 90°C. Adjustable temperature and ventilation ensure

excellent food quality control. ScanBox Banquet Line Combo has capacity for 24 containers in the GN 1/1 standard.

Equipped with ScanBox Digital Control, excenter lock, solid doors, 160 mm lockable wheels, removable U-guide rails with 80 mm spacing, black RAL 9005, 220-230V single phase as standard. The equipment can be easily adapted as required through available extra options.

Do you want to know more?

Contact us at info@scanbox.se
or +46 (0)454-30 83 00

ScanBox
Bringing your food with care

Technical specification

MODEL SERIE: Banquet Line Combo - Fan heating



Product models		BLCFF66
Properties		
Regulator		Digital
Heating system		Element with fan & ventilation (std)
Capacity		
Tray system		GN 2/1
Distance between racks (mm)		80
Number of 65mm trays		12
Maximum load weight per rack (kg)		18
Distance to the first rack (mm)		80
Physical Attributes		
Inside depth (mm)		723 mm
Inside width (mm)		557 mm
Inside height (mm)		573 mm
Outside depth (mm)		910 mm
Outside width (mm)		740 mm
Outside height (mm)		1597 mm
Volume (l)		230 l
Net weight (kg)		92 kg
Spiral Cord		4.5 m
Electrical Attributes		
Rated voltage (V)		220-240V / 1 phase
Rated frequency (Hz)		50-60 Hz Hz
Power Rating (A)		7.52 A
Power (W)		1660 W
IP code		44

Equipment & Accessories

MODEL SERIE: Banquet Line Combo - Fan heating



Castors & Brakes

Default	Castors 160 mm swiveling with brake
1000007	Castors 160 mm, stainless steel, swiveling with brake
1000009	Castors 160 mm, all swiveling w. brakes
1000010	Castors 160 mm, stainless steel, all swiveling w. brakes
1000016	Castors 200 mm w. central brake
1000008	Castors 160 mm, dish washable w. brake
1000004	Castors 200 mm swiveling with brake
1000005	Castors 160 mm reinforced, swiveling with brake
1000015	Castors 160 mm w. central brake
1000006	Castors 200 mm reinforced, swiveling with brake
1000017	Castors 160 mm stainless steel w. central brake

Exterior

Default	Black (RAL 9005)
303010-2	Signature Logo
302030-1	Grey (RAL 7042)
950001	Signature Cover
302020-1	Red (RAL 3003)

Electric System

Default	220-240V - Type CEE 7/7
898294-1	220-240V - Type K
905390	220-240V - Type H
4000556	220-240V - Type L
898208-1	220-240V - Type J
90001	220-240V - Type C
898205-1	220-240V - Type G
905817	220-240V - Type I
898202-1	220-240V - Type G 1,5mm ²
90004	220-240V - Type O
898203-1	220-240V - Type I
90002	220-240V - Type D
4000241	220-240V - Type M

Door

Default	Solid
93002	Glass window
93003	Glass door - available in 2025

Door Handle

Default	Excenter Lock
361004	TapSlam
351008-2	One Grip Handle with Lock
301054-1	One Grip Handle

Logistic System

361020	Central Brake
302002-2	Tow Bar Stainless Steel
302001-3	Tow Bar VE

Accessories

400010-1	Card Holder
400003-1	Eutectic Plate GN 1/1
400002-1	Eutectic Plate Holder Banquet Line
301005-5	Aluminium Shelf GN 1/1
301006-6	Aluminium Shelf GN 2/1
301014-7	Grid Stainless Steel GN 1/1
301019-5	Grid Stainless Steel GN 2/1

www.scanbox.se

Visiting adress ScanBox AB, Ekångsvägen 1. SE-293 40 Olofström, Sweden
Post adress ScanBox AB, P.O. Box 13. SE-293 21 Olofström, Sweden
Telephone +46 (0) 454 30 83 00 | Fax +46 (0) 454 30 83 30
Email info@scanbox.se | VAT SE556446828701

ScanBox
Bringing your food with care