

# Banquet Line Duo

## Fan heating



### Product description

The Banquet Line Duo is manufactured to hold and transport hot food in two separate compartments with GN 2/1 capacity. The box is designed with ScanBox ExP construction that combines optimized insulation performance with high operational reliability and environmentally conscious choices.

The right and left compartments of the box form individual temperature zones, equipped with fan heating that provides fast and uniform heat distribution and can reach operating temperatures up to 90°C in 30 minutes. Digitally adjustable

temperatures ensure excellent food quality control. ScanBox Banquet Line Duo is available in several sizes with a capacity of up to 64 containers in the GN 1/1 standard.

Equipped with ScanBox Digital Control, One grip handle, solid doors, 160 mm lockable wheels, removable U-guide rails with 80 mm spacing, black RAL 9005, 220-230V single phase as standard. The equipment can be easily adapted as required through available extra options.

#### Do you want to know more?

Contact us at [info@scanbox.se](mailto:info@scanbox.se)  
or +46 (0)454-30 83 00

**ScanBox**  
*Bringing your food with care*

# Technical specification

## MODEL SERIE: Banquet Line Duo - Fan heating



| Product models                    | BLDFF12                              | BLDFF16                              |
|-----------------------------------|--------------------------------------|--------------------------------------|
| <b>Properties</b>                 |                                      |                                      |
| Regulator                         | Digital                              | Digital                              |
| Heating system                    | Element with fan & ventilation (std) | Element with fan & ventilation (std) |
| <b>Capacity</b>                   |                                      |                                      |
| Tray system                       | GN 2/1                               | GN 2/1                               |
| Distance between racks (mm)       | 80                                   | 80                                   |
| Number of 65mm trays              | 24                                   | 32                                   |
| Maximum load weight per rack (kg) | 18                                   | 18                                   |
| Distance to the first rack (mm)   | 80                                   | 80                                   |
| <b>Physical Attributes</b>        |                                      |                                      |
| Inside depth (mm)                 | 723 mm                               | 723 mm                               |
| Inside width (mm)                 | 557 mm                               | 557 mm                               |
| Inside height (mm)                | 1047 mm                              | 1367 mm                              |
| Outside depth (mm)                | 910 mm                               | 910 mm                               |
| Outside width (mm)                | 1584 mm                              | 1584 mm                              |
| Outside height (mm)               | 1385 mm                              | 1705 mm                              |
| Volume (l)                        | 422 l                                | 551 l                                |
| Net weight (kg)                   | 160 kg                               | 182 kg                               |
| Spiral Cord                       | 4.5 m                                | 4.5 m                                |
| <b>Electrical Attributes</b>      |                                      |                                      |
| Rated voltage (V)                 | 220-240V / 1 phase                   | 220-240V / 1 phase                   |
| Rated frequency (Hz)              | 50-60 Hz Hz                          | 50-60 Hz Hz                          |
| Power Rating (A)                  | 9 A                                  | 9 A                                  |
| Power (W)                         | 2000 W                               | 2000 W                               |
| IP code                           | 44                                   | 44                                   |

# Equipment & Accessories

## MODEL SERIE: Banquet Line Duo - Fan heating



### Castors & Brakes

|         |  |
|---------|--|
| Default | Castors 160 mm swiveling with brake                      |
| 1000007 | Castors 160 mm, stainless steel, swiveling with brake    |
| 1000009 | Castors 160 mm, all swiveling w. brakes                  |
| 1000010 | Castors 160 mm, stainless steel, all swiveling w. brakes |
| 1000016 | Castors 200 mm w. central brake                          |
| 1000008 | Castors 160 mm, dish washable w. brake                   |
| 1000004 | Castors 200 mm swiveling with brake                      |
| 1000005 | Castors 160 mm reinforced, swiveling with brake          |
| 1000015 | Castors 160 mm w. central brake                          |
| 1000006 | Castors 200 mm reinforced, swiveling with brake          |
| 1000017 | Castors 160 mm stainless steel w. central brake          |

### Exterior

|          |                  |
|----------|------------------|
| Default  | Black (RAL 9005) |
| 303010-2 | Signature Logo   |
| 302030-1 | Grey (RAL 7042)  |
| 950001   | Signature Cover  |
| 302020-1 | Red (RAL 3003)   |

### Door Handle

|          |                           |
|----------|---------------------------|
| Default  | One Grip Handle           |
| 361004   | TapSlam                   |
| 351008-2 | One Grip Handle with Lock |

### Electric System

|          |                                      |
|----------|--------------------------------------|
| Default  | 220-240V - Type CEE 7/7              |
| 898294-1 | 220-240V - Type K                    |
| 905390   | 220-240V - Type H                    |
| 4000556  | 220-240V - Type L                    |
| 898208-1 | 220-240V - Type J                    |
| 90001    | 220-240V - Type C                    |
| 898205-1 | 220-240V - Type G                    |
| 905817   | 220-240V - Type I                    |
| 898202-1 | 220-240V - Type G 1,5mm <sup>2</sup> |
| 90004    | 220-240V - Type O                    |
| 898203-1 | 220-240V - Type I                    |
| 90002    | 220-240V - Type D                    |
| 4000241  | 220-240V - Type M                    |

### Door

|         |                                |
|---------|--------------------------------|
| Default | Solid                          |
| 93002   | Glass window                   |
| 93003   | Glass door - available in 2025 |

### Extras

|          |                      |
|----------|----------------------|
| 301058-1 | Vertical Push Handle |
|----------|----------------------|

### Logistic System

|          |                         |
|----------|-------------------------|
| 361020   | Central Brake           |
| 302002-2 | Tow Bar Stainless Steel |
| 302001-3 | Tow Bar VE              |

### Accessories

|          |                                    |
|----------|------------------------------------|
| 400010-1 | Card Holder                        |
| 400003-1 | Eutectic Plate GN 1/1              |
| 400002-1 | Eutectic Plate Holder Banquet Line |
| 301005-5 | Aluminium Shelf GN 1/1             |
| 301006-6 | Aluminium Shelf GN 2/1             |
| 301014-7 | Grid Stainless Steel GN 1/1        |
| 301019-5 | Grid Stainless Steel GN 2/1        |

[www.scanbox.se](http://www.scanbox.se)

Visiting adress ScanBox AB, Ekångsvägen 1. SE-293 40 Olofström, Sweden

Post adress ScanBox AB, P.O. Box 13. SE-293 21 Olofström, Sweden

Telephone +46 (0) 454 30 83 00 | Fax +46 (0) 454 30 83 30

Email [info@scanbox.se](mailto:info@scanbox.se) | VAT SE556446828701

**ScanBox**  
Bringing your food with care