

Banquet Master Single iCombi

Fan heating



Product description

Banquet Master iCombi Single is designed to hold and transport oven racks from the Rational iCombi series. The rack can be rolled directly from the oven into the box, providing an ergonomic solution for high-volume operations. The box is constructed with ScanBox's ExP technology, combining optimized insulation performance with high operational reliability and environmentally conscious design choices.

The unit features fan-assisted heating, ensuring fast and even heat distribution, capable of reaching operating temperatures of up to 90°C within 30

minutes. Adjustable temperature and ventilation settings allow precise control of food quality. The ScanBox Banquet Master iCombi Single is available in GN 1/1 and GN 2/1 configurations, with capacities for 20 or 40 trays.

Standard features include ScanBox Digital Control, excenter lock, solid door, 160 mm lockable wheels, black RAL 9005 finish, and a 220-230V single-phase connection. The equipment can be easily customized with a range of available options.

Do you want to know more?

Contact us at info@scanbox.se
or +46 (0)454-30 83 00

ScanBox
Bringing your food with care

Technical specification

MODEL SERIE: Banquet Master Single iCombi - Fan heating



Product models	BMSIF20	BMSIF40
Properties		
Regulator	Digital	Digital
Heating system	Element with fan & ventilation (std)	Element with fan & ventilation (std)
Capacity		
Tray system	GN 1/1 GN 2/1	GN 1/1 GN 2/1
Physical Attributes		
Outside depth (mm)	990 mm	1160 mm
Outside width (mm)	770 mm	970 mm
Outside height (mm)	1931 mm	1956 mm
Net weight (kg)	89 kg	120 kg
Electrical Attributes		
Rated voltage (V)	220-240V / 1 phase	220-240V / 1 phase
Rated frequency (Hz)	50-60 Hz	50-60 Hz
Power Rating (A)	7.98 A	7.98 A
Power (W)	1800 W	1800 W
IP code	44	44

Equipment & Accessories

MODEL SERIE: Banquet Master Single iCombi - Fan heating



Castors & Brakes

1000003	Castors 160 mm swiveling with brake
1000007	Castors 160 mm, stainless steel, swiveling with brake
1000009	Castors 160 mm, all swiveling w. brakes
1000010	Castors 160 mm, stainless steel, all swiveling w. brakes
1000016	Castors 200 mm w. central brake
1000008	Castors 160 mm, dish washable w. brake
1000004	Castors 200 mm swiveling with brake
1000005	Castors 160 mm reinforced, swiveling with brake
1000015	Castors 160 mm w. central brake
1000006	Castors 200 mm reinforced, swiveling with brake
1000017	Castors 160 mm stainless steel w. central brake

Electric System

898294-1	220-240V - Type K
905390	220-240V - Type H
4000556	220-240V - Type L
898208-1	220-240V - Type J
90001	220-240V - Type C
898205-1	220-240V - Type G
905817	220-240V - Type I
898202-1	220-240V - Type G 1,5mm ²
90004	220-240V - Type O
898201-1	220-240V - Type CEE 7/7
898203-1	220-240V - Type I
90002	220-240V - Type D
4000241	220-240V - Type M

Exterior

303010-2	Signature Logo
302030-1	Grey (RAL 7042)
950001	Signature Cover
302020-1	Red (RAL 3003)
302040-1	Black (RAL 9005)

Door

93001	Solid
-------	-------

Door Handle

Default	Excenter Lock
---------	---------------

Accessories

400010-1	Card Holder
----------	-------------

www.scanbox.se

Visiting adress ScanBox AB, Ekångsvägen 1. SE-293 40 Olofström, Sweden
Post adress ScanBox AB, P.O. Box 13. SE-293 21 Olofström, Sweden
Telephone +46 (0) 454 30 83 00 | Fax +46 (0) 454 30 83 30
Email info@scanbox.se | VAT SE556446828701

ScanBox
Bringing your food with care