

Ergo Line Combo

Compressor cooling + Fan heating



Product description

Ergo Line Combo is made to hold and transport cold and hot food in two separate compartments. The box is designed with ScanBox ExP construction that combines optimized insulation performance with high operational reliability and environmentally conscious choices.

The lower compartment of the box is equipped with compressor cooling that provides effective temperature distribution down to 3°C. The upper space of the box has a static heating system that can reach operating temperatures of up to 90°C. Adjustable temperature and ventilation ensure

excellent food quality control. ScanBox Ergo Line Combo is available in several sizes and variants with a capacity of up to 12 containers in the GN 1/1 standard.

Equipped with ScanBox Digital Control, excenter lock, solid doors, 160 mm lockable wheels, removable U-guide rails with 80 mm spacing, black RAL 9005, 220-230V single phase as standard. The equipment can be easily adapted as required through available extra options.

Do you want to know more?

Contact us at info@scanbox.se
or +46 (0)454-30 83 00

ScanBox
Bringing your food with care

Technical specification

MODEL SERIE: Ergo Line Combo - Compressor cooling + Fan heating



| Product models | ELCCS66 | ELCCS44 | ELCCS46 | ELCCS48 |
|-----------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| Properties | | | | |
| Regulator | Digital | Digital | Digital | Digital |
| Heating system | Element without fan with ventilation | Element without fan with ventilation | Element without fan with ventilation | Element without fan with ventilation |
| Cooling system | Compressor back mounted (std) | Compressor back mounted (std) | Compressor back mounted (std) | Compressor back mounted (std) |
| Capacity | | | | |
| Tray system | GN 1/1 | GN 1/1 | GN 1/1 | GN 1/1 |
| Distance between racks (mm) | 80 | 80 | 80 | 80 |
| Number of 65mm trays | 12 | 8 | 10 | 12 |
| Maximum load weight per rack (kg) | 9 | 9 | 9 | 9 |
| Distance to the first rack (mm) | 80 | 80 | 80 | 80 |
| Physical Attributes | | | | |
| Inside depth (mm) | 600 mm | 600 mm | 600 mm | 600 mm |
| Inside width (mm) | 352 mm | 352 mm | 352 mm | 352 mm |
| Inside height (mm) | 572 mm | 412 mm | 572 mm | 732 mm |
| Outside depth (mm) | 870 mm | 870 mm | 870 mm | 870 mm |
| Outside width (mm) | 540 mm | 540 mm | 540 mm | 540 mm |
| Outside height (mm) | 1597 mm | 1277 mm | 1437 mm | 1597 mm |
| Volume (l) | 121 l | 174 l | 208 l | 60 l |
| Net weight (kg) | 79 kg | 70 kg | 74 kg | 79 kg |
| Spiral Cord | 4.5 m | 4.5 m | 4.5 m | 4.5 m |
| Electrical Attributes | | | | |
| Rated voltage (V) | 220-240V / 1 phase | 220-240V / 1 phase | 220-240V / 1 phase | 220-240V / 1 phase |
| Rated frequency (Hz) | 50-60 Hz | 50-60 Hz | 50-60 Hz | 50-60 Hz |
| Power Rating (A) | 2.42 A | 2.42 A | 2.42 A | 2.86 A |
| Power (W) | 135 W | 135 W | 135 W | 135 W |
| Power (W) | 350 W | 350 W | 350 W | 450 W |
| IP code | 44 | 44 | 44 | 44 |

Equipment & Accessories

MODEL SERIE: Ergo Line Combo - Compressor cooling + Fan heating



Castors & Brakes

| | |
|----------|--|
| Default | Castors 160 mm swiveling with brake |
| 1000007 | Castors 160 mm, stainless steel, swiveling with brake |
| 1000009 | Castors 160 mm, all swiveling w. brakes |
| 1000010 | Castors 160 mm, stainless steel, all swiveling w. brakes |
| 1000016 | Castors 200 mm w. central brake |
| 1000008 | Castors 160 mm, dish washable w. brake |
| 1000004 | Castors 200 mm swiveling with brake |
| 1000005 | Castors 160 mm reinforced, swiveling with brake |
| 1000015 | Castors 160 mm w. central brake |
| 341006-1 | Castors 400 mm Cross Country |
| 1000006 | Castors 200 mm reinforced, swiveling with brake |
| 1000017 | Castors 160 mm stainless steel w. central brake |

Exterior

| | |
|----------|------------------|
| Default | Black (RAL 9005) |
| 303010-2 | Signature Logo |
| 302030-1 | Grey (RAL 7042) |
| 950001 | Signature Cover |
| 302020-1 | Red (RAL 3003) |

Electric System

| | |
|----------|--------------------------------------|
| Default | 220-240V - Type CEE 7/7 |
| 898294-1 | 220-240V - Type K |
| 905390 | 220-240V - Type H |
| 4000556 | 220-240V - Type L |
| 898208-1 | 220-240V - Type J |
| 90001 | 220-240V - Type C |
| 898205-1 | 220-240V - Type G |
| 905817 | 220-240V - Type I |
| 898202-1 | 220-240V - Type G 1,5mm ² |
| 90004 | 220-240V - Type O |
| 898203-1 | 220-240V - Type I |
| 90002 | 220-240V - Type D |
| 4000241 | 220-240V - Type M |

Door

| | |
|---------|--------------------------------|
| Default | Solid |
| 93002 | Glass window |
| 93003 | Glass door - available in 2025 |

Door Handle

| | |
|----------|---------------------------|
| Default | Excenter Lock |
| 361004 | TapSlam |
| 351008-2 | One Grip Handle with Lock |
| 301054-1 | One Grip Handle |

Logistic System

| | |
|----------|-------------------------|
| 361020 | Central Brake |
| 302002-2 | Tow Bar Stainless Steel |
| 302001-3 | Tow Bar VE |
| 302005 | Ergonomic Base 320 mm |
| 302006 | Ergonomic Base 160 mm |

Extras

| | |
|----------|----------------------|
| 301058-1 | Vertical Push Handle |
|----------|----------------------|

Accessories

| | |
|----------|---------------------------------|
| 400010-1 | Card Holder |
| 400003-1 | Eutectic Plate GN 1/1 |
| 400001-1 | Eutectic Plate Holder Ergo Line |
| 301005-5 | Aluminium Shelf GN 1/1 |
| 301014-7 | Grid Stainless Steel GN 1/1 |

www.scanbox.se

Visiting adress ScanBox AB, Ekångsvägen 1. SE-293 40 Olofström, Sweden
Post adress ScanBox AB, P.O. Box 13. SE-293 21 Olofström, Sweden
Telephone +46 (0) 454 30 83 00 | Fax +46 (0) 454 30 83 30
Email info@scanbox.se | VAT SE556446828701

ScanBox
Bringing your food with care