

# Ergo Line Duo

## Compressor cooling



### Product description

Ergo Line Duo is made to hold and transport cold food in two separate compartments. The box is designed with ScanBox ExP construction that combines optimized insulation performance with high operational reliability and environmentally conscious choices.

The right and left compartments of the box form two individual temperature zones that are equipped with compressor cooling for efficient temperature distribution down to 3°C in 30 minutes. Digitally adjustable temperatures ensure excellent food

quality control. ScanBox Ergo Line Duo is available in several sizes with a capacity of up to 28 containers in the GN 1/1 standard.

Equipped with ScanBox Digital Control, One grip handle, solid doors, 160 mm lockable wheels, removable U-guide rails with 80 mm spacing, black RAL 9005, 220-230V single phase as standard. The equipment can be easily adapted as required through available extra options.

#### Do you want to know more?

Contact us at [info@scanbox.se](mailto:info@scanbox.se)  
or +46 (0)454-30 83 00

**ScanBox**  
*Bringing your food with care*

# Technical specification

## MODEL SERIE: Ergo Line Duo - Compressor cooling



Product models	ELDCC08	ELDCC10	ELDCC12	ELDCC14
<b>Properties</b>				
Regulator	Digital	Digital	Digital	Digital
Cooling system	Compressor back mounted (std)	Compressor back mounted (std)	Compressor back mounted (std)	Compressor back mounted (std)
<b>Capacity</b>				
Tray system	GN 1/1	GN 1/1	GN 1/1	GN 1/1
Distance between racks (mm)	80	80	80	80
Number of 65mm trays	16	16	24	28
Maximum load weight per rack (kg)	9	9	9	9
Distance to the first rack (mm)	80	80	80	80
<b>Physical Attributes</b>				
Inside depth (mm)	600 mm	600 mm	600 mm	600 mm
Inside width (mm)	352 mm	352 mm	352 mm	352 mm
Inside height (mm)	727 mm	727 mm	1047 mm	1207 mm
Outside depth (mm)	870 mm	870 mm	870 mm	870 mm
Outside width (mm)	1100 mm	1100 mm	1100 mm	1100 mm
Outside height (mm)	1065 mm	1225 mm	1385 mm	1545 mm
Volume (l)	154 l	154 l	221 l	255 l
Net weight (kg)	110 kg	125 kg	140 kg	150 kg
Spiral Cord	4.5 m	4.5 m	4.5 m	4.5 m
<b>Electrical Attributes</b>				
Rated voltage (V)	220-240V / 1 phase	220-240V / 1 phase	220-240V / 1 phase	220-240V / 1 phase
Rated frequency (Hz)	50-60 Hz	50-60 Hz	50-60 Hz	50-60 Hz
Power Rating (A)	1.76 A	1.76 A	1.76 A	1.76 A
Power (W)	270 W	270 W	270 W	270 W
IP code	22	22	22	22

# Equipment & Accessories

## MODEL SERIE: Ergo Line Duo - Compressor cooling



### Castors & Brakes

Default	Castors 160 mm swiveling with brake
1000007	Castors 160 mm, stainless steel, swiveling with brake
1000009	Castors 160 mm, all swiveling w. brakes
1000010	Castors 160 mm, stainless steel, all swiveling w. brakes
1000016	Castors 200 mm w. central brake
1000008	Castors 160 mm, dish washable w. brake
1000004	Castors 200 mm swiveling with brake
1000005	Castors 160 mm reinforced, swiveling with brake
1000015	Castors 160 mm w. central brake
1000006	Castors 200 mm reinforced, swiveling with brake
1000017	Castors 160 mm stainless steel w. central brake

### Exterior

Default	Black (RAL 9005)
303010-2	Signature Logo
302030-1	Grey (RAL 7042)
950001	Signature Cover
302020-1	Red (RAL 3003)

### Door Handle

Default	One Grip Handle
361004	TapSlam
351008-2	One Grip Handle with Lock

### Electric System

Default	220-240V - Type CEE 7/7
898294-1	220-240V - Type K
905390	220-240V - Type H
4000556	220-240V - Type L
898208-1	220-240V - Type J
90001	220-240V - Type C
898205-1	220-240V - Type G
905817	220-240V - Type I
898202-1	220-240V - Type G 1,5mm <sup>2</sup>
90004	220-240V - Type O
898203-1	220-240V - Type I
90002	220-240V - Type D
4000241	220-240V - Type M

### Door

Default	Solid
93002	Glass window
93003	Glass door - available in 2025

### Extras

302003-1	Horizontal Push Handle
----------	------------------------

### Logistic System

361020	Central Brake
302002-2	Tow Bar Stainless Steel
302001-3	Tow Bar VE

### Accessories

400010-1	Card Holder
400003-1	Eutectic Plate GN 1/1
400001-1	Eutectic Plate Holder Ergo Line
301005-5	Aluminium Shelf GN 1/1
301014-7	Grid Stainless Steel GN 1/1

[www.scanbox.se](http://www.scanbox.se)

Visiting adress ScanBox AB, Ekångsvägen 1. SE-293 40 Olofström, Sweden

Post adress ScanBox AB, P.O. Box 13. SE-293 21 Olofström, Sweden

Telephone +46 (0) 454 30 83 00 | Fax +46 (0) 454 30 83 30

Email [info@scanbox.se](mailto:info@scanbox.se) | VAT SE556446828701

**ScanBox**  
Bringing your food with care