Food2Go

Fan heating + Compressor cooling





Product description

Food2Go is a mobile serving platform designed to hold and transport both hot and cold food. The box is built with ScanBox's ExP construction, combining optimized insulation performance with high operational reliability and environmentally conscious design choices.

As standard, Food2Go is equipped with two individual heating zones on top and a service surface. Below, there are two separate compartments: one with fan-assisted heating for even heat distribution, capable of reaching operating temperatures up to 90°C, and one with compressor

cooling that chills down to 3°C. Adjustable temperature and ventilation settings ensure precise control of food quality. The compartments have a capacity for 7 hot and 7 cold GN 1/1 containers.

Standard features include a central brake, single-grip handles, and removable U-shaped racks with 80 mm spacing for easy cleaning. The equipment can be customized with additional options such as heating lamps, tray slides, and other accessories to streamline the serving process. Contact us for more information.



Technical specification

MODEL SERIE: Food2Go - Fan heating + Compressor cooling



Postbotomodala	50005
Product models	F2GCF
Properties	Digital
Regulator	Digital
Heating system	Element with fan & ventilation (std)
Cooling system	Compressor back mounted (std)
Capacity	
Tray system	GN 1/1
Distance between racks (mm)	80
Number of 65mm trays	14
Maximum load weight per rack (kg)	9
Distance to the first rack (mm)	65
Physical Attributes	
Outside depth (mm)	780 mm
Outside width (mm)	1320 mm
Outside height (mm)	1357 mm
Net weight (kg)	140 kg
Spiral Cord	4.5 m
Electrical Attributes	
Rated voltage (V)	220-240V / 1 phase
Rated frequency (Hz)	50-60 Hz
Power Rating (A)	4.23 A
Power (W)	130 W
Power (W)	350 W
IP code	22



Equipment & Accessories

MODEL SERIE: Food2Go - Fan heating + Compressor cooling



Exterior		
Default	Black (RAL 9005)	
303010-2	Signature Logo	
302030-1	Grey (RAL 7042)	
950001	Signature Cover	
302020-1	Red (RAL 3003)	
Door Handle		
Default	One Grip Handle	
351008-2	One Grip Handle with Lock	

Electric System	
Default	220-240V - Type CEE 7/7
898294-1	220-240V - Type K
905390	220-240V - Type H
4000556	220-240V - Type L
898208-1	220-240V - Type J
90001	220-240V - Type C
898205-1	220-240V - Type G
905817	220-240V - Type I
898202-1	220-240V - Type G 1,5mm ²
90004	220-240V - Type O
898203-1	220-240V - Type I
90002	220-240V - Type D
4000241	220-240V - Type M
Door	
Default	Solid
Logistic System	
302002-2	Tow Bar Stainless Steel
302001-3	Tow Bar VE
Accessories	
400003-1	Eutectic Plate GN 1/1
400001-1	Eutectic Plate Holder Ergo Line

www.scanbox.se

